



MATERIAL SAFETY DATA SHEET

PJH BRANDS

PRODUCT NAME: PJ1 GOLDFIRE PRO
PRODUCT CODE: 8-16
PRODUCT CLASS: Two Cycle Engine Oil

CONTROL CODE: 8-16

=====

MANUFACTURED FOR: PJH BRANDS
ADDRESS: 8747 E. Via de Commercio, Scottsdale, AZ 85258
EMERGENCY PHONE: CHEMTREC® 703-527-3887 SHIPPER: PJH BRANDS, Contract #CCN17400
DATE REVISED: 9/30/13
INFORMATION PHONE: 1-480-991-8002

-----Emergency Overview-----

Physical State Liquid
Color Purple Odor Mild petroleum odor

DANGER!

Contains Petroleum Distillates. Harmful or fatal if swallowed – Can enter lungs and cause damage. If swallowed, DO NOT induce vomiting. Call a physician immediately.

Combustible Liquid!

Heated material can release vapor that can cause flash fire or ignite with explosive force. Vapor or mists can cause mucous membrane and respiratory tract irritation. Safety glasses are recommended when handling this material. Avoid repeated or prolonged skin contact. Do not store in open or unmarked containers. Spills may create a slipping hazard!

Hazard Ranking

Health Hazard
Fire Hazard
Reactivity

HMIS NFPA

* 1 1
2 2
0 0
* = Chronic Health Hazard

Protective Equipment – See Section 8 for Details

SECTION 1: IDENTIFICATION

Product Number: 8-16
CAS Number: Mixture

Product Family: Two Cycle Engine Oil

SECTION 2: COMPOSITION

Component Name(s)

CAS Registry No. Concentration (%)

1. Highly Refined Petroleum Lubricant Oils	64741-88-4 64742-01-4 64742-54-7 64742-65-0	40 – 60
2. Refined Petroleum Distillates	8052-41-3	10 – 30
3. Proprietary Ingredients	Proprietary Mixture	10 – 30

SECTION 3: HAZARDARDS IDENTIFICATION

Also see Emergency Overview and Hazard Ratings

Major Route(s) of Entry Skin contact

Signs and Symptoms of Acute Exposure

Inhalation At elevated temperatures or in enclosed spaces, product mist or vapors may irate the mucous membranes of the nose, the throat, bronchi, and lungs.

Eye Contact Mild to moderate eye irritation can result from short-term contact with liquid, mist, or vapor.



MATERIAL SAFETY DATA SHEET

PJH BRANDS

Skin Contact	This material can cause mild skin irritation from prolonged or repeated skin contact. Injection under the skin, in muscle, or into the blood stream can cause irritation, inflammation, swelling, fever, and systemic effects and mild central nervous system depression. Injection of pressurized hydrocarbons can cause severe, permanent tissue damage. Initial symptoms may be minor. Injection of petroleum hydrocarbons requires immediate medical attention.
Ingestion	If swallowed, no significant adverse health effects are anticipated. Ingestion can cause a laxative effect. If aspirated into the lungs, liquid can cause severe lung damage or death.
Chronic Health Effects Summary	Prolonged and/or repeated skin contact may cause irritation and inflammation. Symptoms include defatting, redness, dryness, blistering eczema-like lesions, scaly dermatitis, and/or more serious skin disorders. Chronic effects of ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung dysfunction.
Conditions Aggravated by Exposure	Personnel with pre-existing skin disorders, central nervous system (CNS) disease, chronic respiratory diseases, or impaired pulmonary, kidney, and/or liver function should avoid exposure.
Target Organs	Skin, Eyes.
Carcinogenic Potential	This product does not contain any components at concentrations above 0.1% which are considered carcinogenic by OSHA, IARC, or N RTP.

OSHA Hazard Classification is indicated by an "X" in the box adjacent to the hazard title. If no "X" is present, the product does not exhibit the hazard as defined in the OSHA Hazard Communication Standard (29 CFR 1910.1200).

OSHA Health Hazard Classification

Irritant	Toxic
Sensitizer	Highly Toxic
Corrosive	Carcinogenic

OSHA Physical Hazard Classification

Combustible	X	Explosive	Pyrophoric
Flammable		Oxidizer	Water-reactive
Compressed Gas		Organic Peroxide	Unstable

SECTION 4: FIRST AID MEASURES

Take proper precautions to ensure your own health and safety before attempting rescue or providing first aid. For more specific information, refer to Exposure Controls and Personal Protection in Section 8 of this MSDS.

Inhalation	Move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If breathing is difficult, 100 percent humidified oxygen should be administered by a qualified individual. Seek medical attention immediately. Keep the affected individual warm and at rest.
Eye Contact	Check for and remove contact lenses. Flush eyes with cool, clean, low-pressure water while occasionally lifting and lowering eyelids. Seek medical attention if excessive tearing, redness, or pain persists.
Skin Contact	Remove contaminated shoes and clothing. Wipe off excess material. Wash exposed skin with soap and water. Seek medical attention if tissue appears damaged or if irritation persists. Thoroughly clean contaminated clothing before reuse. Discard contaminated leather goods. If material is injected under the skin, into muscle, or into the bloodstream, seek medical attention immediately.
Ingestion	Do not induce vomiting unless directed to by a physician. Do not give anything to drink unless directed to by a physician. Never give anything by mouth to a person who is not fully conscious. If large amounts are swallowed or irritation or discomfort occurs, seek medical attention immediately.



Notes to Physician The viscosity range of the product represented by this MSDS is 100 to 400 SUS at 100° F. Accordingly, upon ingestion there is a low to moderate risk of aspiration. Careful gastric lavage may be considered to evacuate large quantities of material. Subcutaneous or intramuscular injection requires prompt surgical debridement.

SECTION 5: FIRE FIGHTING MEASURES

NFPA Flammability Classification NFPA Class-IIIA combustible liquid. Moderately combustible.

Flash Point Method CLOSED CUP: 61°C (142°F). (Pensky-Martens (ASTM D-93).) OPEN CUP: 101°C (214°F) (Cleveland).

Lower Flammable Limit No data. **Upper Flammable Limit** No data.

Autoignition Temperature No data.

Hazardous Combustion Products Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and trace oxides of sulfur and/or nitrogen.

Special Properties This material will release vapors when heated above the flash point temperature that can ignite when exposed to a source of ignition. In enclosed spaces, vapors can ignite with explosive force. Mists or sprays may burn at temperatures below the flash point.

Extinguishing Media SMALL FIRE: Use dry chemicals, carbon dioxide, foam, water fog, or inert gas (nitrogen). LARGE FIRE: Use foam, water fog, or water spray. Water fog and spray are effective in cooling containers and adjacent structures. However, water can cause frothing and/or may not extinguish the fire. Water can be used to cool the external walls of vessels to prevent excessive pressure, autoignition or explosion. DO NOT use a solid stream of water directly on the fire as the water may spread the fire to a larger area.

Fire Fighting Protective Clothing Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. Withdraw immediately from the area if there is a rising sound from a venting safety device or discoloration of vessels, tanks, or pipelines.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Take proper precautions to ensure your own health and safety before attempting spill control or clean up. For more specific information, refer to the Emergency Overview on Page 1, Exposure Controls and Personal Protection in Section 8 and Disposal Considerations in Section 13 of this MSDS.

Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Slipping hazard; do not walk through spilled material. Stop leak if you can do so without risk. For small spills, absorb or cover with dry earth, sand, or other inert non-combustible absorbent material and place into waste containers for later disposal. Contain large spills to maximize product recovery or disposal. Prevent entry into waterways or sewers. In urban area, cleanup spill as soon as possible. In natural environments, seek cleanup advise from specialists to minimize physical habitat damage. This material will float on water. Absorbent pads and similar materials can be used. Comply with all laws and regulations.

SECTION 7: HANDLING AND STORAGE

Handling Avoid water contamination and extreme temperatures to minimize product degradation. Empty containers may contain product residues that can ignite with explosive force. Do not



pressurize, cut, weld, braze solder, drill, grind or expose containers to flames, sparks, heat or other potential ignition sources. Consult appropriate federal, state and local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers and/or waste residues of this product.

Storage Keep container closed. Store in a cool, dry, well-ventilated area. Do not store with oxidizing agents. Do not store at elevated temperatures or in direct sunlight for extended periods of time. Consult appropriate federal, state and local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers or waste residues of this product.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Controls Good general ventilation should be sufficient to control airborne contaminant levels. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended occupational exposure limits (see below). Ensure that an emergency eye wash station and safety shower are located near the workstation.

Personal Protective Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to OSHA regulations.

Eye Protection Safety glasses equipped with side shields should be adequate protection under most conditions of use. Wear goggles and/or face shield if splashing is anticipated. Wear goggles and face shield if material is heated above 125°F (51°C). Have suitable eye wash water available.

Hand Protection Avoid skin contact. Use gloves (e.g., disposable PVC, neoprene, nitrile, vinyl or PVC/NBR). Wash hands with plenty of mild soap and water before eating, drinking, smoking, use of toilet facilities, or leaving work. DO NOT use gasoline, kerosene, solvents, or harsh abrasive skin cleaners.

Body Protection Use clean and impervious protective clothing (e.g., neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing may include long-sleeve outer garment, apron, or lab coat. If significant contact occurs, remove oil-contaminated clothing as soon as possible and promptly shower. Launder contaminated clothing before reuse or discard. Wear heat protective boots and protective clothing when handling material at elevated temperatures.

Respiratory Protection Vaporization or misting is not expected at ambient temperatures. Therefore, the need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist prefilter should be used. Protection factors vary depending upon the type of respirator used. Respirators should be used in accordance with OSHA requirements (29 CFR 1910.134).

General Comments Use good personal hygiene practices. Wash hands and other exposed skin areas with plenty of mild soap and water before eating, drinking, smoking, use of toilet facilities, or leaving work. DO NOT use gasoline, kerosene, solvents or harsh abrasive skin cleaners. Since specific exposure standards/control limits have not been established for this product, the "Oil Mist, Mineral" exposure limits shown below are suggested as minimum control guidelines.

Occupational Exposure Guidelines

Substance	Applicable Workplace Exposure Levels
1) Oil Mist, Mineral	TWA: 5 STEL: 10 (mg/M ₃) from ACGIH (TLV) TWA: 5 (mg/M ₃) from OSHA (PEL)



MATERIAL SAFETY DATA SHEET

PJH BRANDS

TWA: 5 STEL: 10 (mg/M₃) from NIOSH

2) Refined Petroleum Distillates

TWA: 100 (ppm) from ACGIH (TLV) [2001]
TWA: 500 (ppm) from OSHA (PEL) [1989]

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid	Color	Purple	Odor	Mild petroleum odor
Specific Gravity	0.87 (Water = 1)	pH	Not applicable	Vapor Density	>1 (Air = 1)
Boiling Point/Range	Not available	Melting/Freezing Point	Not available		
Vapor Pressure	<1 mm of Hg (@ 20°C)	Viscosity (cSt @ 40°C)	54		
Solubility in Water	Insoluble in cold water	Volatile Characteristics	182 g/l VOC's W/V		
Additional Properties	API Gravity (ASTM D287) = 31.1 @ 60° F Density = 7.25 Lbs./gal. Viscosity (ASTM D2161) = AP 270 SUS @ 100°F				

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability	Stable.	Hazardous Polymerization	Not expected to occur.
Conditions to Avoid	Keep away from extreme heat, sparks, open flame, and strongly oxidizing conditions.		
Materials Incompatibility	Strong oxidizers.		
Hazardous Decomposition Products	No additional hazardous decomposition products were identified other than the combustion products identified in Section 5 of this MSDS.		

SECTION 11: TOXICOLOGICAL INFORMATION

For other health-related information, refer to the Emergency Overview on Page 1 and the Hazards Identification in Section 3 of this MSDS.

Toxicity Data	Refined Petroleum Distillates:
DERMAL (LD50):	Acute: >3000 mg/kg [Rabbit].
INHALATION (LC50):	Acute:>5.5 mg/L 8 hours [Rat].
Highly-Refined Petroleum Lubricant Oils:	
ORAL (LD50):	Acute: >5000 mg/kg [Rat].
DERMAL (LD50):	Acute: >2000 mg/kg [Rabbit].

Refined Petroleum Distillates:

Studies on laboratory animals have associated similar materials with mild to moderate eye and respiratory tract irritation. Studies on laboratory animals have shown this material to cause skin irritation after repeated or prolonged contact. Human volunteers exposed to an airborne concentration of 400 ppm experienced no ill effect. Saturated vapors in air (or AP 8,200 mg/m₃) are below LC50 level in rats. Based upon laboratory animal studies, repeated direct application of Stoddard Solvent to the skin can produce defatting dermatitis, kidney damage, and changes in blood-forming capacity. Rats developed kidney damage and elevated blood urea nitrogen levels when exposed to a concentration of 1.9 mg/L for 65 days. The kidney damage in rats appeared to involve both the tubules and glomeruli, and occurred only in males. Male rats exposed to airborne concentrations of 100, 150 and 1,500 ppm for 6 hours per day, 5 days per week for 90 days did not develop any functional or



MATERIAL SAFETY DATA SHEET

PJH BRANDS

histological signs of neurotoxicity. This material was determined not to be mutagenic in the

Salmonella/microsome (Ames) assay, the in-vivo mouse bone marrow cell chromosome aberrations assay, or the in-vitro rat sister chromatid exchanges assay.

Highly-Refined Petroleum Lubricant Oils:

Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of mineral oil mists well above applicable workplace exposure levels include lung inflammatory reaction, lipoid granuloma formation and lipoid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists at or near current work place exposure levels produced no significant toxicological effects. In long-term studies (up to two years) no carcinogenic effects have been reported in any animal species tested.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity Analysis for ecological effects has not been conducted on this product. However, if spilled, this product and any contaminated soil or water may be harmful to human, animal, and aquatic life. Also, the coating action associated with petroleum and petroleum products can be harmful or fatal to aquatic life and waterfowl.

Environmental Fate An environmental fate analysis has not been conducted on this specific product. However, plants and animals may experience harmful or fatal effects when coated with petroleum-based products. Petroleum-based (mineral) lube oils will normally float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into water. With time, if not removed, oxygen depletion in the waterway might be enough to cause a fish kill or create an anaerobic environment.

SECTION 13: DISPOSAL CONSIDERATIONS

DOT Status	A U.S. Department of Transportation regulated material.		
Proper Shipping Name	Combustible liquid, n.o.s. (contains Petroleum distillates) [This product has a flash point temperature between 60.5° to 93°C (141° to 200°F). For bulk shipments it is classified as a US DOT "Combustible Liquid". According to 49 CFR 173.150 (f)(2), certain transportation related requirements, such as labeling, might not apply to this product when shipped in non-bulk packaging (e.g., less than 119 gallons capacity). However, pursuant to 49 CFR 173.150 (b) limited-quantities offered for or transported via aircraft may be subject to US DOT regulations.]		
Hazard Class	COMBUSTIBLE LIQUID [with a flash point >60.5°C (>141°F)]	Packing Group(s) UN/NA ID	III NA 1993
Reportable Quantity	A Reportable Quantity (RQ) has not been established for any components of this material.		
Placards	A Combustible placard may not be required for this material when transported in a non-bulk container with a maximum capacity LT 450 L (LT 119 Gal.)		
Emergency Response Guide No.	128		
HAZMAT STCC No.	4915378		
MARPOL III Status	Not a DOT "Marine Pollutant" per 49 CFR 171.8.		

SECTION 15: REGULATORY INFORMATION

TSCA Inventory This product and/or its components are listed on the Toxic Substance Control Act AA-M-8-16X Premix GoldFire Pro



MATERIAL SAFETY DATA SHEET

PJH BRANDS

(TSCA) inventory.

SARA 302/304

The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to Subparts 302 and 304 to submit emergency planning and notification information based on Threshold Planning Quantities (TPQs) and Reportable Quantities (RQs) for "Extremely Hazardous Substances" listed in 40 CFR 302.4 and 40 CFR 355. No components were identified.

SARA 311/312

The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to this subpart to submit aggregate information on chemicals by 'Hazard Category' as defined in 40 CFR 370.2 This material would be classified under the following hazard categories: Fire

SARA 313

This product contains the following components in concentrations above de minimis levels that are listed as toxic chemicals in 40 CFR Part 372 pursuant to the requirements of Section 313 of SARA: No components were identified.

CERCLA

The Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) requires notification of the National Response Center concerning release of quantities of "hazardous substances" equal to or greater than the reportable quantities (RQs) listed in 40 CFR 302.4. As defined by CERCLA, the term "hazardous substance" does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically designated in 40 CFR 302.4. Chemical substances present in this product or refinery stream that may be subject to this statute are: None identified.

CWA

This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.

California Proposition 65

This product is not known to contain any components for which the State of California has found to cause cancer, birth defects or other reproductive harm.

New Jersey Right-to-Know Label

Petroleum Oil (Two Cycle Engine Oil)

Additional Regulatory Remarks

Federal Hazardous Substances Act, related statutes, and Consumer Product Safety Commission regulations, as defined by 16 CFR 1500.14(b)(3) and 1500.83(a)(13): This product contains "Petroleum Distillates" which may require special labeling if distributed in a manner intended or packaged in a form suitable for use in the household or by children. Precautionary label dialogue should display the following: **DANGER: Contains Petroleum Distillates! Harmful or fatal if swallowed! Call Physician Immediately. KEEP OUT OF REACH OF CHILDREN!**

SECTION 16: OTHER INFORMATION

Refer to Page 1 for the HMIS and NFPA Hazard Ratings for this product.

ABBREVIATIONS

AP = Approximately

EQ = Equal

> = Greater Than

< = Less Than

NA = Not Applicable

ND = No Data

NE = Not Established

ACGIH = American Conference of Governmental Industrial Hygienists

AIHA= American Industrial Hygiene Association

IARC = International Agency for Research on Cancer

AA-M-8-16X Premix GoldFire Pro



MATERIAL SAFETY DATA SHEET

PJH BRANDS

NTP = National Toxicology Program

NIOSH = National Institute of Occupational Safety and Health

OSHA=Occupational Safety and Health Administration

NPCA = National Paint and Coating Manufacturers Association

HMIS = Hazardous Materials Information System

NFPA = National Fire Protection Association

EPA = Environmental Protection Agency

DISCLAIMER

THE INFORMATION IN THIS MSDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS MSDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS MSDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE, OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

(8-16) 04/23/02